




Overview

The TR series embedded open frame touch monitors with multi-point (10 points) projected capacitive (PCAP) touch screen deliver an industrial-grade & reliable solution with wide-angle viewing, outstanding image clarity & accurate touch response that is cost-effective for OEMs and systems integrators. Embedded eye-catching & rugged bezel with edge-to-edge glass and ultra-thin & ultra-narrow edge structure design with patent delivers flat design self-service terminals with high durability and scratch & water resistance. Landscape, portrait and face-up orientation ensures flexible mounting possibilities in almost any installation. Our TR series product line is available in a wide range of sizes, offering the versatility needed for commercial kiosk applications from self-service and gaming to industrial automation, digital signage & healthcare.



Features

Embedded Design

Edge-to-edge glass design ensures seamless and flat integration

Easy to Use

Plug & play, flexible video input interface

Full HD

1920 x 1080 resolution

Reliable and Professional Design

Elegant design with metal structure & plastic front bezel delivers outstanding image clarity

Touch Through Enabled with PCAP

Accurate 10 points touch responses support touch through a front layer of glass with thickness's up to 5mm.

Multi-touch

Support Windows multi-touch protocol

Supported OS

Windows 7 /10, Android , Linux, Mac OS X

Flexible Mounting

Different mounting holes & external brackets making flexible mounting possibilities in almost any installation

Specifications

Display

LED Panel	IPS-Panel ,32 inch
Backlight	E-LED (edge-lit)
Viewable Area	697.7 x 392.26mm
Brightness	400cd/m2
Contrast Ratio	1200:1
Viewing Angle	178° H/V
Response Time	8 ms (GTG)
Number of Colors	16.7M Colors
Native Resolution	1920x1080 (16:9), FHD
Video Frequency	60Hz
Video Interface	VGA x1 / HDMI x1
Input Resolution	1920 x 1080 @ 60Hz

Touch

Touch Points	10 (HID, only with supported OS)
Touch Technology	No touch version → WTM320TR-NT
Touch Method	Projective Capacitive (PCAP)
	Finger, glove (latex)
Glass Overlay	Active & passive stylus pen
	4mm tempered glass
Water Resistance	Optional AG / AR surface finish
	Support touch in water fog and light rain
Calibration	Little drops of water will not cause drift
Response Time	16ms
Report Rate	>100Hz
Touch Interface	USB (Type B) x1
Supported OS	Win 7 / 10 / Android / Linux / Mac

OSD Function

OSD Controls	7 buttons / remote control
OSD Languages	CN, EN, FR, IT, DE
	ES, KR, RU, PT
Remote Control Interface	RS232 x 1, support duplex communication remote Control (optional)

Mechanical

Product Dimension	792.8x 487.4x 55.45 mm
Packing Dimension	920x 580x 210 mm (1 PCS)
	1150x 910x 925 mm (12 PCS)
Weight(approx.)	17 kg / 21 kg(1PCS)/230 kg(12PCS)
Wall Mount Method	VESA,MIS-F,200x200 mm,Y,6,90

Electrical

Internal Speakers	Support 8Ω 7W
Power Supply	AC in: 100V~240V (50/60Hz)
Typical Power	≤ 50W (typ.)
Standby Power	≤ 2 W (typ.)

Environmental

Operating T & H	0 °C ~ 50 °C, 90% RH
Storage T & H	-20 °C ~ 60 °C, 90% RH

Accessories

Active Stylus Pen	Included
Mounting Bracket	Wall mount or free standing
OPS PC	Supported

Other

Ready for Use	7/24
Warranty	1Year
Regulations	CCC, CE, FCC, CB, RoHS



Specifications can change without prior notice.

JEA Technologies Pty is the authorized distributor of AnyTouch products in Australia and New Zealand

JEA Technologies Pty Ltd.

Unit 36, 41-49 Norcal Road, Nunawading, Victoria, 3131, Australia Email:
sales@jeatech.com.au
Tel: +61 (0) 3 8736 0330





Tolerance Table	
Dimension Range	Tolerance (mm)
Under 25mm	0.1
25.1-100mm	0.2
100.1-250mm	0.4
250.1-400mm	0.8
400.1-500mm	1.5
500.1-630mm	2.0
630.1-800mm	2.5

Tolerancing

UNLESS OTHERWISE SPECIFIED ALL DIMS ARE mm

Radius	Area	Perimeter
Radius ± 0.15	$\pi \times 0.15^2 \times 2 \approx 0.28$	$2 \times \pi \times 0.15 \approx 0.94$
Radius ± 0.2	$\pi \times 0.2^2 \times 2 \approx 0.50$	$2 \times \pi \times 0.2 \approx 1.26$

Angles $\pm 0.5^\circ$

DO NOT SCALE DRAWING

[illegible]